



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :H01F 7/14, G02F 1/29, G11B 11/10,
13/04

A2

(11) International Publication Number:

WO 96/11484

(43) International Publication Date:

18 April 1996 (18.04.96)

(21) International Application Number: PCT/IB95/00784

(22) International Filing Date: 22 September 1995 (22.09.95)


(30) Priority Data:

94202894.5 6 October 1994 (06.10.94)

EP

(34) Countries for which the regional or
international application was filed:

NL et al.

(81) Designated States: JP, KR, SG, European patent (AT, BE, CH,
DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).**Published***Without international search report and to be republished
upon receipt of that report.*(71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groe-
newoudseweg 1, NL-5621 BA Eindhoven (NL).(71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE];
Kottbygatan 5, Kista, S-164 85 Stockholm (SE).(72) Inventors: JANSEN, Gerardus, Lucien, Mathildus; Groe-
newoudseweg 1, NL-5621 BA Eindhoven (NL). PEIJNEN-
BURG, Antonius, Theodorus, Adrianus; Groenewoudseweg
1, NL-5621 BA Eindhoven (NL).(74) Agent: SCHRIJNEMAEEKERS, Hubert, J., M.; Internationaal
Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven
(NL).(54) Title: ACTUATOR COMPRISING A ROTATABLE MAGNET BODY; ACTUATOR UNIT COMPRISING THE ACTUATOR
AND A CONTROL SYSTEM; MAGNETO-OPTICAL DEVICE COMPRISING THE ACTUATOR, AND SCANNER
COMPRISING THE ACTUATOR

(57) Abstract

The invention relates to an actuator comprising a permanent magnet body (1) and coil means for cooperation with the magnet body. The magnet body is rotatable about an axis of rotation (7) between, for example two, stop positions. The coil means exclusively comprise at least one active coil section (9a, 11a) of an electrical coil, which coil section extends parallel to the axis of rotation of the magnet body and substantially faces a magnet pole in a stop position of the magnet body.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Actuator comprising a rotatable magnet body; actuator unit comprising the actuator and a control system; magneto-optical device comprising the actuator, and scanner comprising the actuator.

The invention relates to an actuator comprising a permanent magnet body which is rotatable between stop positions about an axis of rotation and has magnet poles situated at opposite sides of the axis of rotation, and further comprising coil means for cooperation with the magnet body to move said body from one stop position to another stop position.

The invention further relates to an actuator unit including an actuator comprising a permanent magnet body which is rotatable between stop positions about an axis of rotation and has magnet poles situated diametrically at opposite sides of the axis of rotation, and further comprising coil means for cooperation with the magnet body to move said body from one stop position to another stop position, and including a control system for the actuator, which control system comprises two Hall sensors.

Such an actuator and actuator unit are known from EP 0,271,342 (herewith incorporated by reference). The known actuator serves for rotating a magnet about an axis of rotation for the purpose of magneto-optical recording and comprises the relevant magnet, which is arranged near a magneto-optical recording disc, a first coil surrounding the magnet, and a second coil disposed above the first coil, which is offset from the central axis of the first coil in the circumferential direction of the recording disc. The magnet, which is situated in the centre of the first coil, serves for generating in two stop or end positions a magnetic field which is oriented perpendicularly to the surface of the recording disc. When both coils are energised the magnet, which is in a first stop position, is subjected to a driving force which causes the magnet to be rotated into a second stop position. In the first half of a 180° rotation period the magnet is then accelerated and in the second half it is decelerated. Just before the second stop position is reached the energisation of the second coil is terminated, while the first coil remains energised to maintain the subsequently reached stop position.

The known actuator forms part of an actuator unit, which further comprises a control circuit for controlling the drive currents applied to the first and the

second coil. For the detection of a rotation of the magnet relative to the stop positions two Hall elements are used, one element being secured to an inner surface and another element to an outer surface of the second coil.

A disadvantage of the known actuator and actuator unit is that two coils
5 are needed to obtain the desired rotations of the magnet, which makes the construction bulky and complex. Another disadvantage is that upon energisation of both coils the initial torque exerted on the magnet is small, a maximal torque being reached only after a certain rotation. As a result of this, it is difficult to realise large accelerations of the magnet starting from a stop position and large decelerations until a well-defined stop position of the magnet is
10 reached. A further disadvantage is that the first coil is energised permanently, which requires a continuous supply of electric power.

It is an object of the invention to provide an actuator and an actuator unit
which are of simple construction and which can produce rapid rotations of the magnet body
15 with a comparatively low electric power.

The actuator in accordance with the invention is characterised in that the coil means exclusively comprise at least one active coil section of a coil, which coil section extends at least substantially parallel to the axis of rotation of the magnet body and substantially faces one of the magnet poles in the stop positions of the magnet body. When
20 the coil means are energised the special arrangement of the active coil section results in a driving magnetic dipole perpendicular to the dipole of the permanent magnet body in one of the stop positions. An advantage of this is that when the coils means are energised in the stop positions a high initial torque is generated on the magnet body, so that only a very short time is required to move the magnet body from the one stop position into the other stop position.
25 Another advantage is the low power consumption. Moreover, the actuator in accordance with the invention has the advantage that its construction is compact and simple and only a small overall height is required. The magnet body is preferably rod-shaped with a longitudinal axis coinciding with the axis of rotation and can have a circular or square cross-section oriented transversely of the axis of rotation. The north pole and the south pole of a pair of magnet
30 poles are preferably disposed diametrically.

It is to be noted that EP 0,222,916 (herewith incorporated by reference) discloses an actuator having a rotatable rod-shaped permanent magnet for generating a bias field for the purpose of magnet recording, which actuator comprises a drive coil which completely surrounds the magnet. In order to enable a driving force to be generated in the

stop or rest positions of the magnet the magnet and the drive coil occupy mutually offset positions, the axis of rotation of the magnet and the central longitudinal coil axis, which extends parallel to the axis of rotation, being spaced apart. The actuator further comprises one Hall element secured to a mounting plate and disposed opposite the magnet. A
5 disadvantage of this known actuator is that after energisation of the drive coil a small initial driving torque is exerted on the magnet, which occupies a stop position. The torque does not increase until the magnet is in rotation. As a result, it is difficult to realise rapid well-defined stepwise movements.

An embodiment of the actuator in accordance with the invention is
10 characterised in that there are provided means, not being coil means, for holding the magnet body in the stop positions. An advantage of this embodiment is that preferential positions coinciding with the stop positions can be realised in a passive manner.

An embodiment of the actuator in accordance with the invention is
characterised in that a further active coil section extends parallel to the active coil section,
15 said coil sections substantially facing one of the magnet poles in the stop positions of the magnet body. Owing to the presence of two active coil sections the coil means can generate an at least substantially wholly symmetrical magnetic field. An advantage of this is that the actuator exhibits an at least substantially wholly uniform torque characteristic, as a result of which exactly defined rotations of the magnet body can be realised by means of a simple
20 drive.

An embodiment of the actuator in accordance with the invention is
characterised in that said means not being coil means comprise a ferromagnetic element
which extends parallel to the axis of rotation of the magnet body and substantially faces one
of the magnet poles in the stop positions of the magnet body. The provision of a
25 ferromagnetic element, such as a soft-iron strip, creates preferential positions based on reluctance effects, reluctance forces ensuring that the magnet body is held in one of the preferential positions, *i.e.* the stop positions. An advantage of this is that an active control system or mechanism is not needed, which may result in a substantial saving of energy. The reluctance effects assist in maintaining the stop positions of the magnet body in two ways. A
30 reluctance torque counteracts a rotation of the magnet body from one of the preferential positions and a force draws the permanent magnet body towards the ferromagnetic element. Since the magnet body is supported by a bearing means the last-mentioned force is compensated for by normal forces in the bearing means, the friction in the bearing means,

which preferably comprises two bearings between which the magnet body extends, counteracts a rotation of the magnet body when the coil means are not energised.

An embodiment of the actuator in accordance with the invention is characterised in that the ferromagnetic element forms part of a ferromagnetic plate-shaped body to which the coil means are secured, which coil means extend between the plate-shaped body and the magnet body. The presence of the ferromagnetic plate-shaped body in the direct proximity of the active coil section or the active coil sections short-circuits a part of the magnetic circuit of the active coil section or sections, so that the coil means generate an intensified magnetic field, which considerably improves the drive efficiency.

An embodiment of the actuator in accordance with the invention is characterised in that the plate-shaped body has upright edge portions between which the magnet body and the coil means extend. As a result of this measure, the plate-shaped body used in the actuator in accordance with the invention has a magnetic shielding function in addition to the other functions already mentioned. The plate-shaped body both counteracts the leakage of internal magnetic fields and the penetration of external magnetic fields into the actuator. The last-mentioned aspect is of particular importance in order to prevent a position, such as a preferential position, of the magnet body from being disturbed. A further advantage of the presence of upright wall portions is that it mitigates a possible adverse effect of inactive coil sections of the drive coil or drive coils.

The actuator unit in accordance with the invention is characterised in that an actuator in accordance with the invention is used, the Hall sensors of the control system, in the stop positions of the magnet body, being disposed at opposite sides of a plane which contains the axis of rotation and is oriented transversely of one of the magnet poles, the control system comprising a matrix unit having a first input and a second input for signals issuing from the Hall sensors. The Hall sensors supply signals which depend on the perpendicular magnetic induction of the magnetic field at the location of the sensors. During rotation of the magnet body, which has a north pole and a south pole, signals are generated which vary sinusoidally in dependence upon the angle of rotation of the magnet body and which are shifted in phase relative to one another. Surprisingly, it has been found that adding and subtracting these signals results in signals which are measures of both the position and the positional error of the magnet body and which consequently enable the coil means to be controlled so as to obtain a desired position of the magnet body. It is to be noted that a matrix unit is to be understood to mean an arithmetic or adder/subtractor unit.

An embodiment of the actuator unit in accordance with the invention is characterised in that the matrix unit has a first output for a signal representing a positional error of the magnet body and a second output for a signal representing an instantaneous position of the magnet body, the control system comprising a first control unit connected to
5 the first output of the matrix unit and a second control unit connected to the second output of the matrix unit, which second control unit has an input for a signal representing a desired position of the magnet body, the first control unit and the second control unit being interconnected and each being connected to an amplifier unit for energising the coil means. During use of the actuator unit the first control unit compares the desired position with the
10 instantaneous position of the magnet body. If there is a difference between the two last-mentioned positions a pulse is applied to the amplifier unit in order to rotate the magnet body. For an exact approach to the desired position the second control unit drives the first control unit for a given time interval.

The invention further relates to a magneto-optical device comprising a
15 turntable for a magneto-optical disc, which turntable is rotatable about an axis of rotation, and comprising a unit for recording information and further comprising an actuator in accordance with the invention or an actuator unit in accordance with the invention, the axis of rotation of the magnet body of the actuator extending at least substantially perpendicularly to the axis of rotation of the turntable. The magneto-optical disc intended here has an
20 information layer which can be inscribed by means of a radiation beam, particularly a laser beam, produced by a radiation source and aimed at the information layer, and an external magnetic field, also referred to as bias field, present at the information layer. By locally heating the information layer by means of an optical beam the coercive field strength of the material in the information layer is reduced in such a manner that the local magnetisation in
25 the information layer becomes equal to the magnetisation of the bias field. The polarity of the bias field then determines the local polarity in the information layer, which polarity is retained by the information layer after turn-off of the radiation source. By means of a permanent magnet a substantial magnetic induction can be realised without consumption of energy. Magneto-optical recording requires, for example, an induction of 300 Gauss
30 measured at a distance of 1 mm from the magnet. This can be achieved by with a rod-shaped magnet body of NdFeB having a square cross-section of $0.80 \times 0.80 \text{ mm}^2$.

The magneto-optical device in accordance with the invention can be used for the storage of audio and/or video and/or data information.

For reversing the polarity of the bias field required for magneto-optical recording the preferably rod-shaped magnet body, which has magnet poles at two opposite longitudinal surfaces parallel to the axis of rotation, should be rotated through 180° about the axis of rotation, which coincides with the longitudinal axis of the magnet body. By means of
5 the actuator in accordance with the invention this can be effected in a very efficient and rapid manner, a polarity reversal being possible within, for example, 1 ms.

The invention further relates to another suitable application of the actuator in accordance with the invention or the actuator unit in accordance with the invention, *i.e.* a scanner. A scanner is known *per se* from Photonics Spectra, December 1992, pp. 98-100;
10 Kevin R. Sharp (herewith incorporated by reference). The known scanner is a two-dimensional bar code scanner and comprises a housing with a laser diode, a mirror arrangement and a photodetector. The mirror arrangement comprises two mirrors which are rotatable with different speeds about two mutually perpendicular axes by means of two resonant drive elements.

15 The scanner in accordance with the invention comprises a radiation source and further comprises an actuator in accordance with the invention or an actuator unit in accordance with the invention, a lateral surface of the magnet body which extends parallel to the axis of rotation of the magnet body of the actuator being provided with a mirror or a mirror surface for reflecting a radiation beam issuing from the radiation source. An
20 advantage of the scanner in accordance with the invention *inter alia* resides in the efficient drive system for the mirror, which is not restrained by a resonant drive element. Moreover, the preferably rod-shaped magnet body results in a minimal moving mass.

An embodiment of the scanner in accordance with the invention is characterised by the presence of a further actuator in accordance with the invention or a
25 further actuator unit in accordance with the invention comprising a further actuator, a lateral surface of the magnet body of the further actuator being provided with a mirror for reflecting a radiation beam issuing from the radiation source and the axis of rotation of the actuator making an angle with the axis of rotation of the magnet body of the further actuator. The axes of rotation of said magnet bodies preferably make an angle of 90° with one another.
30 Thus, one of said actuators provides deflection of the radiation beam from the radiation source, particularly a laser source, in a first direction, for example the X direction in a system of orthogonal axes, and the other actuator provides deflection in a second direction, for example the Y direction. By mutually different drives of the actuators a scanning beam emanating from the scanner can perform any desired scanning movement over a surface on

which the beam is incident. This makes it possible, for example, to form a Lissajous figure or to perform a line scan.

The invention will now be described in more detail, by way of example,
5 with reference to the drawings, in which

Figure 1A is a diagrammatic plan view showing a first embodiment of the actuator in accordance with the invention,

Figure 1B is a sectional view I_B-I_B of the actuator shown in Figure 1A,

Figure 1C is a sectional view I_C-I_C of the actuator shown in Figure 1A,

10 Figure 2 is a diagrammatic perspective view showing a part of a second embodiment of the actuator in accordance with the invention,

Figure 3A is a diagrammatic plan view showing a third embodiment of the actuator in accordance with the invention,

Figure 3B is a sectional view III_B-III_B of the actuator shown in Figure 3A,

15 Figure 3C is a sectional view III_C-III_C of the actuator shown in Figure 3A,

Figure 4 is a block diagram showing a control system of an embodiment of the actuator unit in accordance with the invention,

Figure 5 shows diagrammatically an embodiment of the magneto-optical device in accordance with the invention,

20 Figure 6A is a diagrammatic plan view showing an embodiment of the scanner in accordance with the invention, and

Figure 6B is a perspective view of the scanner shown in Figure 6A.

The actuator in accordance with the invention shown in Figures 1A, 1B
25 and 1C comprises a magnet body 1 formed by a permanent magnet of, for example, NdFeB. The permanent magnet body 1 is rod-shaped and in the present embodiment it is of square cross-section and has at its axial ends circularly cylindrical end journals 3, which form part of a bearing means 5 mounted in a frame. The bearing means 5, which defines an axis of rotation, comprises for example two plain bearings. The magnet used in the magnet body 1
30 has one pair of magnet poles N and Z, situated at opposite sides of the longitudinal axis of the magnet body 1, which axis coincides with the axis of rotation 7.

The actuator further comprises coil means, in the present example formed by two active coil sections 9a and 11a of two, for example flat, electrical coils 9 and 11,

respectively. The active coil sections 9a and 11a, hereinafter also referred to as active coil section and further active coil section, extend parallel to the axis of rotation 7.

The actuator further comprises means, not being coil means, for holding the magnet body 1 in two stop positions. These means include a ferromagnetic element 13, which in the present example is constituted by a soft-iron strip which extends parallel to the axis of rotation. The element 13 ensures that when the coil means are not energised the magnet body 1 is in a first stop position, in which the south pole Z faces the element 13 as shown in Figures 1A-1C, or in a second stop position, in which the north pole N faces the element 13. As is apparent from the drawing, the active coil sections 9a and 11a are so arranged that they face a magnet pole in the stop positions of the magnet body 1. In the present embodiment the element 13 is situated on a ferromagnetic plate-shaped body 15 with which it is integral or to which it is secured. The body 15 comprises two upright wall portions 15a, which extend parallel to the axis of rotation 7 and between which the magnet body 1 and the active coil sections 9a and 11a extend. The other inactive coil sections 29b and 31b of the coils 29 and 31 are situated mainly outside the area bounded by the upright wall portions 15a.

If desired, the actuator may be provided with two Hall sensors 17a and 17b to determine the position of the magnet body 1. The Hall sensors 17a and 17b are mounted on the plate-shaped body 15 and are disposed at opposite sides of the axis of rotation 7.

The actuator in accordance with the invention shown in Figure 2 comprises a permanent magnet body 21 which is rotatable between stop positions about an axis of rotation 27. In the present example the basically rod-shaped magnet body 21 is of square cross-section and consequently has four identical longitudinal or outer surfaces. The magnet body 21 may have one or two pairs of magnet poles. The drawing shows only one pair of magnet poles Z, N. At its axial ends the magnet body 21 has round end journals 23 supported in stationary bearing elements 25. In Figure 2 only one bearing is shown.

The actuator further has coil means, which exclusively comprise a first active coil section 29a and a second active coil section 31a. Both active coil sections 29a and 31a extend parallel to the axis of rotation 27 and in the stop positions of the magnet body 21 they face one of the magnet poles. The actuator further comprises a ferromagnetic plate-shaped body 35 with an element 33 facing one of the magnet poles in the stop positions of the magnet body 35. The plate-shaped body 35, which carries the active coil sections 29a and 31a of the coils 29 and 31, further comprises two upright shielding edge portions 35a.

The actuator in accordance with the invention shown in Figures 3A, 3B and 3C comprises a permanent magnet body 51 and a coil 59 having one active coil section 59a. The magnet body 51 is elongate, is of round or circularly cylindrical cross-section, is supported in two bearings 55 and is rotatable about an axis of rotation 57. The magnet body is diametrically magnetised, has two magnet poles N and Z at opposite sides of the axis of rotation and has two stop positions. The actuator coil means formed by the active coil section 59a extends parallel to the axis of rotation 57, is situated opposite the magnet body 51 and faces one of the magnet poles in the stop positions of the magnet body 51.

The actuator further comprises a ferromagnetic plate 65 with a ferromagnetic element 63 and upright wall portions 65a. The element 63, which faces the magnet body 51, is for example cam-shaped or strip-shaped and serves to secure the stop positions of the magnet body 51 when the coil means is not energised. The actuator further has two Hall sensors 67a and 67b in a similar way as shown in Figures 1A and 1B.

Together with the example of a control system shown in Figure 4 the actuator shown in Figures 1A-1C or 3A-3C forms an embodiment of the actuator unit in accordance with the invention.

The block diagram in Fig. 4, which shows the electronic control system of the actuator unit, comprises four blocks, i.e. a first block I, which represents a matrix unit, a second block II, which represents a second control unit, a third block III, which represents a first control unit, and a fourth block, which represents an amplifier unit IV. The matrix unit I has two inputs a_1 and a_2 for applying two signals from the Hall sensors, designated H_1 and H_2 in Figure 4, and the second control unit II has an input b for applying a signal representing the desired position of the magnet body of the actuator in accordance with the invention. Although the Hall sensors measure a leakage field of the magnet body, which may be disturbed by the presence of the plate-shaped body, it is possible to generate sine and cosine signals, respectively by adding and subtracting the signals from the Hall sensors. The sum of the signals from the Hall sensors provides information about the position of the magnet body and, as a consequence, about the polarity of the magnet pole facing the Hall sensors, whereas the difference provides information about the positional error of the magnet body.

The matrix unit I has two outputs, of which an output c_1 is connected to an input d_1 of the first control unit III and an output c_2 is connected to an input b_2 of the second control unit II. The second control unit II has two outputs, of which an output e_1 is connected to the input d_2 of the first control unit and an output e_2 is connected to an input f_1 .

of the amplifier unit IV. The amplifier unit IV further has an input f_2 , to which an output g of the first control unit is connected, and an output h , which is connected to the coil means, denoted by the letter C in Figure 4, of the actuator in accordance with the invention.

The control system operates as follows. A request for a certain magnetic
5 field direction, which is caused by a certain position or orientation of the magnet body, is presented to the second control II. The second control unit then determines whether the instantaneous magnetic field direction, which is dictated by the instantaneous position of the magnet body, corresponds to the desired direction. This is achieved in that in the second control unit II the desired position signal is compared with the position signal from the
10 matrix unit I. If the two signals are identical no action is taken; if there is a difference the coil means C are energised via the amplifier unit IV to move the magnet body of the actuator from one stop position to another stop position, the first control unit III ensuring an exact approach to the desired position of the magnet body by means of the positional error signal from the matrix unit I.

The magneto-optical device in accordance with the invention shown in
15 Figure 5 includes an embodiment of the actuator unit in accordance with the invention. The actuator unit comprises, for example, the actuator shown in Figures 1A-1C and the control system shown in Figure 4. The actuator, which bears the reference numeral 80 in Figure 5, comprises the permanent magnet body 1, which is supported in the bearing means 5, is
20 rotatable between two stop positions about an axis of rotation 7 and has magnet poles N and Z at opposite sides of the axis of rotation 1, and further comprises coil means for cooperation with the magnet body 1, in order to rotate the magnet body 1 from one stop position, for example as shown, into another stop position, which in the present example is reached after a rotation through 180° . The coil means comprise at least one active coil
25 section of an electrical coil, which coil section extends parallel to the axis of rotation 7 and in the stop positions faces a magnet pole N or Z. This embodiment has two active coil sections 9a and 11a, of which Figure 5 only shows the coil section 9a. The coil sections are mounted on the ferromagnetic plate-shaped body 15.

The magneto-optical device shown in Figure 5 further comprises a
30 turntable 84 which is rotatable about an axis of rotation 82 and is drivable by an electric motor. The turntable serves to support a disc-shaped record carrier 86, particularly a magneto-optical recording disc, having a recordable and/or readable magneto-optical (MO) layer 86a. The axis of rotation 82 of the turntable 84 extends perpendicularly to the axis of rotation 7 of the magnet body 1. The device shown in Figure 5 further comprises a unit 90

for recording and/or reading information. The unit 90 *inter alia* comprises a light source 92, particularly a laser device, an objective 97 for projecting a focused radiation spot on the MO layer 86a, a beam splitter 96, and a photodetector 98. If desired, a mirror 100 may be used, as in the present example. The objective 94 is preferably movable in focusing directions
5 transverse to the MO layer 86a by drive means, which are not shown here and are known *per se*. Moreover, the objective 94 is supported to be movable in a radial direction relative to the axis of rotation 82. For this purpose the present example uses a slide 104 which is movable along a rectilinear guide 102. The guide 102 extends parallel to the basically radially oriented axis of rotation 7 of the magnet body 1. In operation of the device 80,
10 particularly during recording in the magneto-optical disc 86, an alternating bias field is required, particularly a magnetic field with magnetic vectors oriented transversely of the MO layer 86a. A request for a desired magnetic polarity from a disc controller is then applied to the second control unit (see Figure 4, block II) of the control system.

The scanner in accordance with the invention shown in Figures 6A and 6B
15 has two actuators in accordance with the invention, for example two actuators as shown in Figure 2. Of these actuators only the magnet bodies are shown. The scanner is intended for 2D scanning and comprises a radiation source 292, particularly a laser source, a first actuator in accordance with the invention having a magnet body 201a, which is rotatable about an axis of rotation 207a, and having a second actuator in accordance with the invention
20 having a magnet body 201b, which is rotatable about an axis of rotation 207b. The elongate or rod-shaped magnet bodies each have at least one reflecting longitudinal or lateral surface 202a and 202b, respectively, for deflecting a radiation beam 294 produced by the radiation source 292. The axis of rotation 207a extends perpendicularly to the axis of rotation 207b. Viewed in a system of orthogonal axes XYZ the body 201a produces a deflection of the
25 radiation beam 294 in an X direction and the body 201b produces a deflection in a Y direction in a projection area 296. By separately driving the actuators it is in principle possible to perform any desired scanning movement over the area 296. The beam of light reflected from the projection area 296 contains information about this area and is detected by an optical detection system.

30 It is to be noted that the scope of the invention is not limited to the exemplary embodiments disclosed herein.

CLAIMS:

1. An actuator comprising a permanent magnet body which is rotatable between stop positions about an axis of rotation and has magnet poles situated at opposite sides of the axis of rotation, and further comprising coil means for cooperation with the magnet body to move said body from one stop position to another stop position,
5 characterised in that the coil means exclusively comprise at least one active coil section of a coil, which coil section extends at least substantially parallel to the axis of rotation of the magnet body and substantially faces one of the magnet poles in the stop positions of the magnet body.
2. An actuator as claimed in Claim 1, characterised in that there are
10 provided means, not being coil means, for holding the magnet body in the stop positions.
3. An actuator as claimed in Claim 1 or 2, characterised in that a further active coil section extends parallel to the active coil section, said coil sections substantially facing one of the magnet poles in the stop positions of the magnet body.
4. An actuator as claimed in Claim 2 or Claims 2 and 3, characterised in
15 that said means not being coil means comprise a ferromagnetic element which extends parallel to the axis of rotation of the magnet body and substantially faces one of the magnet poles in the stop positions of the magnet body.
5. An actuator as claimed in Claim 4, characterised in that the ferromagnetic element forms part of a ferromagnetic plate-shaped body to which the coil means are
20 secured, which coil means extend between the plate-shaped body and the magnet body.
6. An actuator as claimed in Claim 5, characterised in that the plate-shaped body has upright edge portions between which the magnet body and the coil means extend.
7. An actuator unit including an actuator comprising a permanent magnet body which is rotatable between stop positions about an axis of rotation and has magnet poles
25 situated diametrically at opposite sides of the axis of rotation, and further comprising coil means for cooperation with the magnet body to move said body from one stop position to another stop position, and including a control system for the actuator, which control system comprises two Hall sensors, characterised in that an actuator as claimed in any one of the preceding Claims is used, the Hall sensors of the control system, in the stop positions of the

magnet body, being disposed at opposite sides of a plane which contains the axis of rotation and is oriented transversely of one of the magnet poles, the control system comprising a matrix unit having a first input and a second input for signals issuing from the Hall sensors.

8. An actuator unit as claimed in Claim 7, characterised in that the matrix

5 unit has a first output for a signal representing a positional error of the magnet body and a second output for a signal representing an instantaneous position of the magnet body, the control system comprising a first control unit connected to the first output of the matrix unit and a second control unit connected to the second output of the matrix unit, which second control unit has an input for a signal representing a desired position of the magnet body, the
10 first control unit and the second control unit being interconnected and each being connected to an amplifier unit for energising the coil means.

9. A magneto-optical device comprising a turntable for a magneto-optical disc, which turntable is rotatable about an axis of rotation, and comprising a unit for recording information and further comprising an actuator as claimed in any one of the Claims
15 1 to 6 or an actuator unit as claimed in Claim 7 or 8, the axis of rotation of the magnet body of the actuator extending at least substantially perpendicularly to the axis of rotation of the turntable.

10. A scanner comprising a radiation source and further comprising an actuator as claimed in any one of the Claims 1 to 6 or an actuator unit as claimed in Claim 7
20 or 8, a lateral surface of the magnet body, which surface extends parallel to the axis of rotation of the magnet body of the actuator, being provided with a mirror for reflecting a radiation beam issuing from the radiation source.

11. A scanner as claimed in Claim 10, characterised in by the presence of a further actuator as claimed in any one of the Claims 1 to 6 or a further actuator unit as
25 claimed in Claim 7 or 8 comprising a further actuator, a lateral surface of the magnet body of the further actuator being provided with a mirror for reflecting a radiation beam issuing from the radiation source and the axis of rotation of the actuator making an angle with the axis of rotation of the magnet body of the further actuator.

2/5




FIG. 2







FIG. 4

3/5



4/5




FIG. 5

5/5




FIG. 6A





FIG. 6B



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G11B 11/10, H01F 7/14		A3	(11) International Publication Number: WO 96/11484
			(43) International Publication Date: 18 April 1996 (18.04.96)
(21) International Application Number: PCT/IB95/00784		(81) Designated States: JP, KR, SG, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 22 September 1995 (22.09.95)			
(30) Priority Data: 94202894.5 6 October 1994 (06.10.94) EP (34) Countries for which the regional or international application was filed: NL et al.		Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).		(88) Date of publication of the international search report: 17 October 1996 (17.10.96)	
(71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 5, Kista, S-164 85 Stockholm (SE).			
(72) Inventors: JANSEN, Gerardus, Lucien, Mathildus; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). PEIJNENBURG, Antonius, Theodorus, Adrianus; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).			
(74) Agent: SCHRIJNEMAEEKERS, Hubert, J., M.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).			

(54) Title: ACTUATOR COMPRISING A ROTATABLE MAGNET BODY; ACTUATOR UNIT COMPRISING THE ACTUATOR AND A CONTROL SYSTEM; MAGNETO-OPTICAL DEVICE COMPRISING THE ACTUATOR, AND SCANNER COMPRISING THE ACTUATOR



(57) Abstract

The invention relates to an actuator comprising a permanent magnet body (1) and coil means for cooperation with the magnet body. The magnet body is rotatable about an axis of rotation (7) between, for example two, stop positions. The coil means exclusively comprise at least one active coil section (9a, 11a) of an electrical coil, which coil section extends parallel to the axis of rotation of the magnet body and substantially faces a magnet pole in a stop position of the magnet body.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LJ	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 95/00784

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: G11B 11/10, H01F 7/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: G11B, H01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

CLAIMS, WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5291345 A (YOSHIKI UMEDA ET AL), 1 March 1994 (01.03.94), column 1, line 12 - line 43; column 6, line 52 - column 7, line 28, figures 1,14	1,3,9
Y	--	7
X	US 5351221 A (TAKEHIDE OHNO), 27 Sept 1994 (27.09.94), column 5, line 20 - column 6, line 40, figures 5,6	1,9
Y	--	7

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

26 August 1996

Date of mailing of the international search report

27 -08- 1996

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Bo Gustavsson
Teleph ne No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 95/00784

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0566989 A2 (SONY CORPORATION), 27 October 1993 (27.10.93), column 3, line 17 - line 56, figures 3, 4	1,3,9
A	--	7
A	US 5345431 A (THOMAS C. OLIVER ET AL), 6 Sept 1994 (06.09.94), column 7, line 17 - column 9, line 2, figures 5,6 -----	2,4,5,7

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 95/00784

B x I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

- I. Claims 1-6 and 7-8 define one invention relating to an actuator and an actuator unit comprising a rotatable magnet body.
- II. Claim 9 defines a magneto-optical device for recording purposes, wherein an actuator according to any of the claims 1-8 is used.
- III. Claims 10 and 11 define a scanner for optically scanning an object, wherein an actuator according to any of the claims 1-8 is used.

There is no technical relationship among these inventions involving one or more of the same or corresponding special technical features. (As defined in Rule 13.2)

However, claim 9 could be searched together with claims 1-8 without justifying an additional fee.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.: 1-8 and 9

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT
Information on patent family members

31/07/96

International application No.
PCT/IB 95/00784

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 5291345	01/03/94	JP-A- 4079001	12/03/92
US-A- 5351221	27/09/94	JP-A- 3224148	03/10/91
EP-A2- 0566989	27/10/93	JP-A- 5303790	16/11/93
US-A- 5345431	06/09/94	JP-A- 6180802	28/06/94
		US-A- 5490124	06/02/96